

Paris, 16th May, 2025

Watchdata Technologies
Europarc de Pichaury
1330 rue Guilibert de la Lauzière, Bât B8
13856 AIX-EN-PROVENCE CEDEX 3
FRANCE

Calypso® Compliance Certificate - Card product

Certificate Number: CNA-CCPR-00033

Product/System name: TimeCOS DI Calypso Prime 3.2 (commercial identification)

Compliant with: Calypso Prime Specification (V3.3.E2)

Type of product : PRIME Dual Card

RF Protocol supported: Type B

Calypso platform reference: \$50 SLC36 Family

Mode: Regular mode, Extended mode

Main features: PIN, Stored values, Shared files

Dear Customer,

PayCert hereafter referred to as the Certification Body, has received a request, submitted by Watchdata Technologies, your company, hereafter referred to as the Vendor for the Certification of the Dual card product "TimeCOS DI Calypso Prime 3.2" (Hardware identification: SLC36PDL352 S11, Hardware Manufacturer ID: Infineon Technologies AG, Software Issuer ID: WATCHDATA \$15, Application version: V1.1), hereafter referred to as the Product and identified above as "TimeCOS DI Calypso Prime 3.2".

In connection with your request, we have received your Implementation Conformance Statement (ICS), referred to as CAL.WDT.PRIME.2023-029 dated 2025/05/12 and we have assessed your Test Report(s) (ref. IC.E.RE.2501.018 V1.0), which was generated by ICUBE Testing Center, following the Test Plan (ref. 121003-TL-CalypsoPrime-TestPlan version 6).

After assessing such files in the Certification Evaluation Report (ref. CER/EVR/CNA/2024-145 v4.0.0) the Certification Body has found reasonable evidence that the submitted samples of the Product comply to the Calypso Prime specification (ref. 060708-SP-CalypsoPrime_v3.3E2 (July 2022)).



48 rue Montmartre 75002 Paris Tél: +33 (0)1 42 61 80 40 www.paycert.eu

The Certification Body hereby grants the Product Certification of compliance with the requirements stated by the Calypso Calypso Prime specification (ref. 060708-SP-CalypsoPrime_v3.3E2 (July 2022)) standard and will include your Product in the certified products list, published on PayCert website (http://cna-paycert-certification.com).

Please note that the present Certification (ref. CER/CLE/CNA/2025-072 v1.0.0) is subject to the following terms and conditions as listed hereafter:

- i) The Vendor commits to the Certification Body certification procedures as well as the Calypso Certification Policy to obtain the Certification and therefore is valid as of today and will expire on the 15 May 2035.
- ii) If the Product's hardware or software is changed, the Vendor must notify the Certification Body of this fact in writing. Any change in the certified Product that generates a different behaviour of the Product with respect to the endorsed specifications and Vendor's Implementation Conformance Statement, in The Certification Body's sole discretion, will be considered a modification subject to a requirement of new certification evaluation.
- iii) The present Certification granted to Watchdata Technologies for the above referenced Product is non-transferable to any other vendor.

The Certification Body has the right to terminate or revoke the Certification should any of the aformentionned terms and conditions be not respected.

Because The Certification Body's grant is subject to such limitations, including certain events of termination, the Vendor and any third parties should confirm that such Certification is current and has not been terminated by referring to the list of certified Products published on the Certification Body website (https://www.cna-paycert-certification.eu).

Certificate Number: CNA-CCPR-00033

This Certificate letter is effective as a proof of Certification.

Name: Laurence MASSON

Title: Chief Operating Officer



APPENDIX (extract from ICS CAL.WDT.PRIME.2023-029 dated 2025/05/12)

Main options				
INTERFACE	Does the product support Contact interface?	YES		
	ISO/IEC 7816-3 protocol If Contact interface supported.	⊠T=0 □ T=1		
SIZE/CAPACITY	What is the maximum value of the Session Modifications byte of the Startup Information supported? The value of the Session Modification field of a Calypso Prime application shall be between 7 and 55 (decimal).	17 (num/hexa)		
	What is the maximum number of records in a file?	250		
	What is the maximum record size supported?	250		
	What is the maximum Lc supported?	250		
	What is the maximum Le supported?	250		
SIZE/CAPACITY	What is the maximum size of binary file supported by the product? Maximum value is 32,768bytes (8000h).	8000h		
	What is the maximum number of data bytes entering a given Session MAC/Session signature? Limit range from 16,384 to 49,152 bytes.	16384		
	What is the minimal/maximal size of the certification authority public key certificate (CACert) that can be stored?	Min.: NA		
	If PKI mode supported.	Max.: NA		
	What is the minimal/maximal size of the Calypso Prime application public key certificate (CardCert) that can be stored?	Min.: NA		
	If PKI mode supported.	Max.: NA		



Applicability declaration for compatibility with legacy terminal

Object	Constraint linked	Applicability supported
CLA byte '94' supported for the Select Application Command	CLA_94_SEL	⊠ Yes □ No
CLA byte '94' supported for the other Calypso command	CLA_94	⊠ Yes □ No
CLA byte 'FA' supported	CLA_FA	⊠ Yes □ No
DES key supported	DES	⊠ Yes □ No
DESX key supported	DESX	⊠ Yes □ No
Historical bytes of ATR readable using GET DATA	GET_ATR	⊠ Yes □ No
Ratification on contactless deselection	RAT_ON_DESELECT	⊠ Yes □ No

<u>Comment</u>: Product based on Calypso Specification v3.2 and does not implement "Pre-Open Variant". Ratification is shared between applications

No Traceability information readable using GET DATA

Applicability declaration for native product

Object	Constraint linked	Applicability supported
List of Application available through ISO APDU Command (cf Calypso Prime specification version 3.3 edition 2 §4.3)	APP_AV	⊠ Yes □ No
Default application selected at reset		□ Yes ⊠ No
	DEF APP	
If "yes", indicate which is the default application at reset (i.e. at opening of a logical channel).	_	Click here to enter your text.
DF contains another DF	DF_IN_DF	□ Yes ⊠ No
Get response for a partial read of available bytes on the card supported ⁴	GETRESP_PARTIAL	⊠ Yes □ No
Master File supported	MF	⊠ Yes □ No
Select Command without request for FCI supported	NO_FCI	⊠ Yes □ No
PUT DATA (for AID) supported	PUT_AID	⊠ Yes □ No
PUT DATA (for SV link) supported	PUT_SV_LINK	⊠ Yes □ No

⁴ This option is only available on contact interface