

Paris, 08 December 2025

#### Paragon ID

Parc d'activité de l'Argile / 123 Chemin de l'Argile - Voie K 460 Avenue de Quiera 06370 Mouans-Sartoux FRANCE

### Calypso® Compliance Certificate - Card product

Certificate Number: CNA-CCPR-00037

Product/System name: TanGO PRIME v3 (commercial identification)

Compliant with: Calypso Prime Specification (V3.3.E2)

Type of product : PRIME Contactless card

RF Protocol supported: Type B, Innovatron (Type B')

Calypso platform reference: \$52 SLC26 Family

Mode: Regular mode, Extended mode

Main features: PIN, Stored values, Shared files

Dear Customer.

PayCert hereafter referred to as the Certification Body, has received a request, submitted by Paragon ID, your company, hereafter referred to as the Vendor for the Certification of the Contactless card product "TanGO PRIME v3" (Hardware identification: SLC26TDA280G7, Hardware Manufacturer ID: Infineon Technologies AG, Software Issuer ID: PARAGON ID \$00, Application version: v3 r1), hereafter referred to as the Product and identified above as "TanGO PRIME v3".

In connection with your request, we have received your Implementation Conformance Statement (ICS), referred to as CAL.PRG.PRIME.2025-016 dated 2025/10/24 and we have assessed your Test Report(s) (ref. IC.E.RE.2510.008 V1.1), which was generated by ICUBE TESTING CENTER, following the Test Plan (ref. 121003-TL-CalypsoPrime-TestPlan version 8).

After assessing such files in the Certification Evaluation Report (ref. CER/EVR/CNA/2025-144 v1.0.0) the Certification Body has found reasonable evidence that the submitted samples of the Product comply to the Calypso Prime specification (ref. 060708-SP-CalypsoPrime\_v3.3E2 (July 2022)).



The Certification Body hereby grants the Product Certification of compliance with the requirements stated by the Calypso Calypso Prime specification (ref. 060708-SP-CalypsoPrime\_v3.3E2 (July 2022)) standard and will include your Product in the certified products list, published on PayCert website (http://cna-paycert-certification.com).

Please note that the present Certification (ref. CER/CLE/CNA/2025-177 v1.0.0) is subject to the following terms and conditions as listed hereafter :

- i) The Vendor commits to the Certification Body certification procedures as well as the Calypso Certification Policy to obtain the Certification and therefore is valid as of today and will expire on the 07 December 2035.
- ii) If the Product's hardware or software is changed, the Vendor must notify the Certification Body of this fact in writing. Any change in the certified Product that generates a different behaviour of the Product with respect to the endorsed specifications and Vendor's Implementation Conformance Statement, in The Certification Body's sole discretion, will be considered a modification subject to a requirement of new certification evaluation.
- iii) The present Certification granted to Paragon ID for the above referenced Product is non-transferable to any other vendor.

The Certification Body has the right to terminate or revoke the Certification should any of the aformentionned terms and conditions be not respected.

Because The Certification Body's grant is subject to such limitations, including certain events of termination, the Vendor and any third parties should confirm that such Certification is current and has not been terminated by referring to the list of certified Products published on the Certification Body website (<a href="https://www.cna-paycert-certification.eu">https://www.cna-paycert-certification.eu</a>).

Certificate Number: CNA-CCPR-00037

This Certificate letter is effective as a proof of Certification.

Name: Laurence MASSON

Title: Chief Operating Officer



### APPENDIX (extract from ICS CAL.PRG.PRIME.2025-016 dated 2025/10/24)

Main options				
INTERFACE	Does the product support Contact interface?	NO		
	ISO/IEC 7816-3 protocol  If Contact interface supported.	□T=0 □ T=1		
SIZE/CAPACITY	What is the maximum value of the Session Modifications byte of the Startup Information supported?	10/0Ah (430 bytes) (num/hexa)		
	The value of the Session Modification field of a Calypso Prime application shall be between 7 and 55 (decimal).			
	What is the maximum number of records in a file?	250		
	What is the maximum record size supported?	250		
	What is the maximum Lc supported?	250		
	What is the maximum Le supported?	250		
SIZE/CAPACITY	What is the maximum size of binary file supported by the product?  Maximum value is 32,768bytes (8000h).	8191 (1FFFh)		
	What is the maximum number of data bytes entering a given Session MAC/Session signature?  Limit range from 16,384 to 49,152 bytes.	49152		
	What is the minimal/maximal size of the certification authority public key certificate (CACert) that can be stored?	Min.: N/A		
	If PKI mode supported.	Max.: N/A		
	What is the minimal/maximal size of the Calypso Prime application public key certificate (CardCert) that can be stored?	Min.: N/A		
	If PKI mode supported.	Max.: N/A		



# Applicability declaration for compatibility with legacy terminal

Object	Constraint linked	Applicability supported
CLA byte '94' supported for the Select Application Command	CLA_94_SEL	⊠ Yes □ No
CLA byte '94' supported for the other Calypso command	CLA_94	⊠ Yes □ No
CLA byte 'FA' supported	CLA_FA	⊠ Yes □ No
DES key supported	DES	⊠ Yes □ No
DESX key supported	DESX	⊠ Yes □ No
Historical bytes of ATR readable using GET DATA	GET_ATR	□ Yes ⊠ No
Ratification on contactless deselection	RAT_ON_DESELECT	⊠ Yes □ No

## **Applicability declaration for native product**

Object	Constraint linked	Applicability supported
List of Application available through ISO APDU Command (cf Calypso Prime specification version 3.3 edition 2 §4.3)	APP_AV	□ Yes ⊠ No
Default application selected at reset		□ Yes ⊠ No
	DEF_APP	
If "yes", indicate which is the default application at reset (i.e. at opening of a logical channel).		
DF contains another DF	DF_IN_DF	□ Yes ⊠ No
Get response for a partial read of available bytes on the card supported <sup>4</sup>	GETRESP_PARTIAL	□ Yes ⊠ No
Master File supported	MF	□ Yes ⊠ No
Select Command without request for FCI supported	NO_FCI	⊠ Yes □ No
PUT DATA (for AID) supported	PUT_AID	⊠ Yes □ No
PUT DATA (for SV link) supported	PUT_SV_LINK	□ Yes ⊠ No

<sup>&</sup>lt;sup>4</sup> This option is only available on contact interface