



PayCert
48 rue Montmartre
75002 Paris
France

Paris, 27th October 2022

M. Laurent BROCHARD
INGENICO
9 Avenue de la Gare Rovaltain TGV
26958 VALENCE
France

CEN TS 16794 Compliance Certificate - PCD

A Smart Ticketing Alliance certification program

Certificate Number: CNAPC/PCD-00035
Product/System name: Open/2500 (commercial identification)
Compliant with : CEN/TS 16794-1:2017
Operational temp. range : Class D testing (-25°C to +55°C)

Dear M. Laurent BROCHARD,

The certification Body PayCert has received a request, submitted by INGENICO France SAS, your company, for the Certification of the PCD product Open/2500 (PCD Hardware version: V01; PCD Software version: V01.01), hereafter referred to as the Product and identified above as "Open/2500".

In connection with your request, we have received your Implementation Conformance Statement (ICS), referred to as PAY.ING.PCD.CEN16794.2017.2022-007 and we have assessed your Test Report(s) (ref. IC.E.RE.2205.008 V1.0 (Analog); IC.E.RE.2205.009 V1.0 (Digital)), which was generated by ICUBE, following the Test Plan "CEN/TS 16794-2:2017".

Based on these elements, as indicated in PayCert's Certification Report (ref. CER/EVR/PCD/2022-002 V1.0.0) the Certification Body has found reasonable evidence that the submitted samples of the Product complies to the CEN/TS TECHNICAL SPECIFICATION 16794-1:2017 Public transport -Communication between contactless readers and fare media.

The Certification Body hereby grants the Product Certification of compliance with the requirements stated by the CEN/TS 16794-1:2017 standard and will include your Product in the certified products list, published on PayCert website (www.cna-paycert-certification.com).



PayCert
48 rue Montmartre
75002 Paris
France

Please note that the present Certification is subject to the following terms and conditions as listed hereafter :

i) The present Certification is granted on the basis of the Smart Ticketing Alliance Certification Policy and therefore is valid as of today and will expire on the 27. October 2029.

ii) If the Product is changed, INGENICO France SAS must notify the Certification Body of this fact in writing. Any change in the Product that may generate a different behaviour with respect to the CEN/TS 16794-1:2017 standard or a difference in the Product Implementation Conformance Statement will be considered a major modification subject to a new evaluation in order to maintain the present Certification.

iii) The present Certification granted to INGENICO France SAS for the above referenced Product is non-transferable to any other vendor.

The Certification Body has the right to terminate or revoke the Certification should any of the aforementioned terms and conditions be not respected.

INGENICO France SAS, Certificate Number: CNAPC/PCD-00035

Name: Ludovic VERECQUE

Title: General Manager



Certification / n°5-0563
Portée disponible sur
www.cofrac.fr



PayCert
48 rue Montmartre
75002 Paris
France

a. PCD Product Description

[PCD1] Administrative data

[PCD1.1] (*) Brand name: Ingenico

[PCD1.2] (*) Trade name: Open/2500

[PCD1.3a] (*) PCD Hardware version: V01

[PCD1.3b] (*) PCD Software version: V01.01

[PCD1.4] (*) Reference of the contactless reader or antenna module: T3PCD4UA0 V1.0

[PCD1.4a] (*) Hardware version of the contactless reader or antenna module: V1.0

[PCD1.4b] (*) Software version of the contactless reader or antenna module: V01.01

[PCD1.5] (*) EMVCo Approval number (if applicable): 17812 0322 310 31a 31a ICUB

The PCD is based on a STA certified PCD (*): Yes

If yes STA PCD certificate number (*): CNAPC/PCD-00031

If yes rationale to justify the delta-certification (*): The contactless interface (PCD) is implemented in 2 different product form factors : OPEN1500 and OPEN2500. This is the same PCD Hardware and Software. No impact in the casing change

b. PCD General Technical Characteristics

[PCD2.1] (*) PT Reader Type: IFM Reader (Full range A and B)

[PCD2.2] (*) Transaction supported when more than one PICC in the field: No

[PCD2.3] (*) Operational temperature range supported: Class D (-25°C to + 55°C)

[PCD2.7] (*) Reference of the PCD Zero Point – Range A (target ID marked on sample or photo or diagram) :



[PCD2.11] (*) Reference of the PCD Zero Point – Range B (target ID marked on sample or photo or diagram)

Idem Range A



PayCert
48 rue Montmartre
75002 Paris
France

c. PCD Supported Options

[PCD3] Protocol characteristics

[PCD3.1] (*) Other supported communication signal interface(s) or protocol(s): none

[PCD4] Type A

[PCD4.1] (*) PCD -> PICC bit rates supported: fc/128 (~106 kbit/s)

Other: -

[PCD4.2] (*) PICC -> PCD bit rates supported: fc/128 (~106 kbit/s)

Other: -

[PCD5] Type B

[PCD5.1] (*) PCD -> PICC bit rates supported: fc/128 (~106 kbit/s)

Other: -

[PCD5.2] (*) PICC -> PCD bit rates supported: fc/128 (~106 kbit/s)

Other: -

d. PCD Test Parameters

[PCD6.2c] (*) PCD internal output buffer size (used for Maximum size of UT_APDU): 256 octets

[PCD6.2d] (*) PCD internal input buffer size (used for Maximum size of response UT_APDU): 256 octets