



PayCert
48 rue Montmartre
75002 Paris
France

Paris, 22. December 2023

FLOWBIRD
Parc Lafayette, 6 rue Isaac Newton
25075 Besançon Cedex 9
France

CEN TS 16794 Compliance Certificate - PCD

A smart Ticketing Alliance certification program

Certificate Number: CNAPC/PCD-00040
Product/System name: Infigo4 (commercial identification)
Compliant with : CEN/TS 16794-1 :2017
Operational temp. range : Class D (-25 °C to + 55 °C)

Dear Customer,

The Certification Body PayCert has received a request, submitted by FLOWBIRD, your company, for the Certification of the PCD product Infigo4 (PCD Hardware version: Revision 1, PCD Software version: v3.0), hereafter referred to as the Product and identified above as "Infigo4".

In connection with your request, we have received your Implementation Conformance Statement (ICS), referred to as PAY.FLO.PCD.CEN16794.2017.2023-007 dated 12/06/2023 and we have assessed your Test Report(s) (ref. IC.E.RE.2305.010 v1.0, IC.E.RE.2305.011 v1.0), which was generated by ICUBE, following the Test Plan "CEN/TS 16794-2:2017".

Based on these elements, as indicated in PayCert's Certification Report (ref. CER/EVR/PCD/2023-178 v1.0.0) the Certification Body has found reasonable evidence that the submitted samples of the Product complies to the CEN/TS 16794-1 :2017.

The Certification Body hereby grants the Product Certification of compliance with the requirements stated by the CEN/TS 16794-1 :2017 standard and will include your Product in the certified products list, published on PayCert website (www.cna-paycert-certification.com).



PayCert
48 rue Montmartre
75002 Paris
France

Please note that the present Certification is subject to the following terms and conditions as listed hereafter :

i) The present Certification is granted on the basis of the Smart Ticketing Alliance Certification Policy and therefore is valid as of today and will expire on the 22 December 2030

ii) If the Product is changed, FLOWBIRD must notify the Certification Body of this fact in writing. Any change in the Product that may generate a different behaviour with respect to the CEN/TS 16794-1 :2017 standard or a difference in the Product Implementation Conformance Statement will be considered a major modification subject to a new evaluation in order to maintain the present Certification.

iii) The present Certification granted to FLOWBIRD for the above referenced Product is non-transferable to any other vendor.

The Certification Body has the right to terminate or revoke the Certification should any of the aforementioned terms and conditions be not respected.

FLOWBIRD, Certificate Number: CNAPC/PCD-00040

Name: Ludovic VERECQUE

Title: General Manager



Certification / n°5-0563
Portée disponible sur
www.cofrac.fr



PayCert
48 rue Montmartre
75002 Paris
France

a. PCD Product Description

[PCD1] Administrative data

[PCD1.1] (*) Brand name: Flowbird

[PCD1.2] (*) Trade name: Infigo 4

[PCD1.3a] (*) Hardware version: Revision 1

[PCD1.3b] (*) Software version: v3.0

[PCD1.4] (*) Reference of the contactless reader or antenna module: INF214 Revision 1

[PCD1.4a] (*) Hardware version of the contactless reader or antenna module: Revision 1

[PCD1.4b] (*) Software version of the contactless reader or antenna module: ClessStack 3.0

[PCD1.5] (*) EMVCo Approval number (if applicable): N/A

The PCD is based on a STA certified PCD (*): Yes No

If yes STA PCD certificate number (*): -

If yes rationale to justify the delta-certification (*): -

b. PCD General Technical Characteristics

[PCD2.1] (*) PT Reader Type:

IFM reader (full range A and B)

Common reader (limited range A and B)

[PCD2.2] (*) Transaction supported when more than one PICC in the field: Yes No

[PCD2.3] (*) Operational temperature range supported:

Class A (Ambient)

Class D (-25 °C to + 55 °C)

[PCD2.7] (*) Reference of the PCD Zero Point – Range A (target ID marked on sample or photo or diagram)





PayCert
48 rue Montmartre
75002 Paris
France

[PCD2.11] (*) Reference of the PCD Zero Point – Range B (target ID marked on sample or photo or diagram)



c. PCD Supported Options

[PCD3] Protocol characteristics

[PCD3.1] (*) Other supported communication signal interface(s) or protocol(s): N/A

[PCD4] Type A

[PCD4.1] (*) PCD -> PICC bit rates supported: fc/128 (~106 kbit/s)

Other: N/A

[PCD4.2] (*) PICC -> PCD bit rates supported: fc/128 (~106 kbit/s)

Other: N/A

[PCD5] Type B

[PCD5.1] (*) PCD -> PICC bit rates supported: fc/128 (~106 kbit/s)

Other: N/A

[PCD5.2] (*) PICC -> PCD bit rates supported: fc/128 (~106 kbit/s)

Other: N/A

d. PCD Test Parameters

[PCD6] Test parameters

[PCD6.2c] (*) PCD internal output buffer size (used for Maximum size of UT_APDU): 512

[PCD6.2d] (*) PCD internal input buffer size (used for Maximum size of response UT_APDU): 512