

Paris, 26/11/2021

Mr. Bruno BARONNET Thales DIS France SA ZI Athelia IV, av. du Jujubier 13705 La Ciotat France

CEN TS 16794 Compliance Certificate - PICC

A Smart Ticketting Alliance certification program

 Certificate Number:
 CNAPC/PIC-00033

 Product/System name:
 Gemalto Calypso G2 Full Contactless (commercial identification)

Compliant with : CEN/TS 16794-1:2017

Operational temp. range : Class I (-10°C to +50°C)

ISO 14443 antenna class : Class 1

Protocol supported : type B

Dear Mr. BARONNET,

The Certification Body PayCert has received a request, submitted by Thales DIS France SA, your company, for the Certification of the PICC product Gemalto Calypso G2 Full Contactless (IC type: SLC32PDL300-H13, Application Type: Calypso V 1.0, Antenna : THALES DIS antenna (0115GALA), Card body : PET-PVC, Protocols : Type B, contactless card), hereafter referred to as the Product and identified above as "Gemalto Calypso G2 Full Contactless".

In connection with your request, we have received your Implementation Conformance Statement (ICS), referred to as PAY.THA.PICC.CEN16794.2017.2021-006 and we have assessed your Test Report (ref. IC.E.RE.2110.029 V1.0 - Analog), which was generated by ICUBE, following the Test Plan "CEN/TS 16794-2:2017".

Based on these elements, as indicated in PayCert's Certification Report (ref. CER/EVR/PIC/2021-146 v1.0.0) the Certification Body has found reasonable evidence that the submitted samples of the Product complies to the CEN/TS 16794-1:2017.

The Certification Body hereby grants the Product Certification of compliance with the requirements stated by the CEN/TS 16794-1:2017 standard and will include your Product in the certified products list, published on PayCert website (<u>www.cna-paycert-certification.com</u>).



Please note that the present Certification is subject to the following terms and conditions as listed hereafter :

i) The present Certification is granted on the basis of the Smart Ticketing Alliance Certification Policy and therefore is valid as of today and will expire on the 22. November 2028.

ii) If the Product is changed, Thales DIS France SA must notify the Certification Body of this fact in writing. Any change in the Product that may generate a different behaviour with respect to the CEN/TS 16794-1:2017 standard or a difference in the Product Implementation Conformance Statement will be considered a major modification subject to a new evaluation in order to maintain the present Certification.

iii) The present Certification granted to Thales DIS France SA for the above referenced Product is non-transferable to any other vendor.

The Certification Body has the right to terminate or revoke the Certification should any of the aformentionned terms and conditions be not respected.

The present certification letter supersedes the certification letter ref. PURE_CLE_PIC_2021-146 v1.0.0 issued on 22/11/2021



Name: Ludovic VERECQUE

Title: General Manager



a. PICC Product Description

[PICC1] Administrative data

- [PICC1.1] (*) Brand name: Gemalto Calypso G2 FC
- [PICC1.2] (*) Trade name: Gemalto Calypso G2 FC
- [PICC1.3a] (*) Hardware version: SLC32PDL300-H13
- [PICC1.3b] (*) Software version: V1.0
- C Yes 🖲 No [PICC1.4] (*) PICC features ISO/IEC 7816 contact interface (dual):
- [PICC1.5] (*) IC manufacturer: Infineon
- [PICC1.6] (*) IC reference / size: SLC32PDL300-H13

The PICC is based on a STA certified PICC (*): Yes No If yes STA PICC certificate number (*): CNAPC/PIC-00025

If yes rationale to justify the delta-certification (*): same OS and chip but card is Full Contactlesss where CNSPC/PIC-0025 is Dual

b. ICC General Technical Characteristics

[PICC2] General technical characteristics

[PICC2.2] (*) Reference of PICC Zero Point (target ID-marked on sample or photo or diagram):



0115GALA Antenna

PICC Zero Point is located at the center of the card

[PICC2.3] (*) Operational temperature range supported:

Class A (Ambient)

Class I (-10 °C to + 50 °C)

[PICC2.4] (*) Antenna class according to ISO/IEC 14443:

O Unclassified



c. PICC Supported Options

[PICC3] Protocol characteristics

•				
	[PICC3.1] (*)	Protocol(s) supported: Type A	🗆 Туре В 🛛	⊠ Other:
[PICC5] Type B (where applicable)				
	[PICC5.1] (*)	PCD -> PICC bit rates supported Other: 212 kbit/s	: 🖲 fc/128	(~106 kbit/s)
	[PICC5.2] <mark>(*)</mark>	PICC -> PCD bit rates supported Other: 212 kbit/s	: 🖲 fc/128	(~106 kbit/s)
	[PICC5.3] <mark>(*)</mark>	Only symmetrical bit rates supp	oorted: C	Yes 💿 No
	[PICC5.4] <mark>(*)</mark>	PUPI value: • Fixed number	er O F	Random number
	[PICC5.9] <mark>(*)</mark>	Extended ATQB support:	Yes	O No
		If yes, SFGI: 4-SGFT4.832ms		
	[PICC5.10] <mark>(</mark> *	S(PARAMETERS) support:	C Yes	No
	[PICC5.11] <mark>(</mark> *	All AFIs are supported: C Yes	🖲 No	
If not, indicate all supported AFI(s): 00h				
	[PICC5.12] <mark>(</mark> *	REQB/WUPB with N > 1 suppor	t: 🖲 Yes	O No