

Paris, 10/08/2023

IDEMIA France SAS 2 place Samuel de Champlain 92400 COURBEVOIE France

CEN TS 16794 Compliance Certificate - PICC

A Smart Ticketting Alliance certification program

Certificate Number: CNAPC/PIC-00041

Product/System name: cityGo Fly 40 (commercial identification)

Compliant with: CEN/TS 16794-1:2017

Operational temp. range: Class I (-10°C to +50°C)

ISO 14443 antenna class: Unclassified

Protocol supported: type B

Dear Customer,

The Certification Body PayCert has received a request, submitted by IDEMIA France SAS, your company, for the Certification of the PICC product cityGo Fly 40 (IC type: SLC36PDL352, Application Type: Calypso CNA Applet v1.3.10/ Calypso Prime Rev 3, Antenna: J2021-77, Card body: PVC, Protocols: Type B, Contactless card), hereafter referred to as the Product and identified above as "cityGo Fly 40".

In connection with your request, we have received your Implementation Conformance Statement (ICS), referred to as PAY.IDE.PICC.CEN16794.2017.2023-009 dated 10/07/2023 and we have assessed your Test Report(s) (ref. IC.E.RE.2306.005_v1.0), which was generated by ICUBE TESTING CENTER, following the Test Plan "CEN/TS 16794-2:2017".

Based on these elements, as indicated in PayCert's Certification Report (ref. CER/EVR/PIC/2023-099 v1.0.0) the Certification Body has found reasonable evidence that the submitted samples of the Product complies to the CEN/TS 16794-1:2017.

The Certification Body hereby grants the Product Certification of compliance with the requirements stated by the CEN/TS 16794-1:2017 standard and will include your Product in the certified products list, published on PayCert website (www.cna-paycert-certification.com).



Please note that the present Certification is subject to the following terms and conditions as listed hereafter:

- i) The present Certification is granted on the basis of the Smart Ticketing Alliance Certification Policy and therefore is valid as of today and will expire on the 26. July 2030.
- ii) If the Product is changed, IDEMIA France SAS must notify the Certification Body of this fact in writing. Any change in the Product that may generate a different behaviour with respect to the CEN/TS 16794-1:2017 standard or a difference in the Product Implementation Conformance Statement will be considered a major modification subject to a new evaluation in order to maintain the present Certification.
- iii) The present Certification granted to IDEMIA France SAS for the above referenced Product is non-transferable to any other vendor.

The Certification Body has the right to terminate or revoke the Certification should any of the aformentionned terms and conditions be not respected.

The present certification letter supersedes the certification letter ref. CER CLE PIC 2023-099 v1.0.0 issued on 26/07/2023

Name: Ludovic VERECQUE

Title: General Manager





a. PICC Product Description

PICC1.1] (*) Brand name: cityGo Fly 40

[PICC1.2] (*) Trade name: cityGo Fly 40

[PICC1.3a] (*) Hardware version: SOLVO FLY 40 v01.00.09

[PICC1.3b] (*) Software version: SOLVO FLY 40 v01.00.09

[PICC1.4] (*) PICC features ISO/IEC 7816 contact interface (dual): Yes No

[PICC1.5] (*) IC manufacturer: Infineon

[PICC1.6] (*) IC reference / size: SLC36PDL352

[PICC1.9] (*) Type of card body structure: PVC

The PICC is based on a STA certified PICC (*): Yes No


If yes STA PICC certificate number (*): Click here to enter text.

If yes rationale to justify the delta-certification (*): Click here to enter text.

b. PICC General Technical Characteristics

[PICC2] General technical characteristics

[PICC2.2] (*) Reference of PICC Zero Point (target ID-marked on sample or photo or diagram):



J2021-77

[PICC2.3] (*) Operational temperature range supported:

Class A (Ambient)

• Class I (-10 °C to + 50 °C)

[PICC2.4] (*) Antenna class according to ISO/IEC 14443:

● Unclassified ○ "Class 1" ○ "Class 2" ○ "Class 3"



c. PICC Supported Options

[PICC3] Protocol chara	acteristics
[PICC3.1] (*) S	Supported communication signal interface(s) and protocol(s): Type A \Box Type B
	other: Click here to enter text.
[PICC4] Type A (where	e applicable)
[PICC4.1] (*) P	PCD -> PICC bit rates supported:
C	Other: Click here to enter text.
[PICC4.2] (*) P	PICC -> PCD bit rates supported:
C	Other: Click here to enter text.
[PICC4.3] (*) C	Only symmetrical bit rates supported:
[PICC4.5] (*) U	JID value: C Fixed number C Random number
[PICC4.11] (*) S	(PARAMETERS) support: C Yes C No
[PICC5] Type B (where	e applicable)
[PICC5.1] (*) P	PCD -> PICC bit rates supported:
C	Other: 212 and 424 kbit/s
[PICC5.2] (*) P	PICC -> PCD bit rates supported:
C	Other: 212 and 424 kbit/s
[PICC5.3] (*) C	Only symmetrical bit rates supported:
[PICC5.4] (*) P	PUPI value: Fixed number C Random number
[PICC5.9] (*) E	extended ATQB support: C Yes • No
If	f yes, SFGI: 0
[PICC5.10] (*) S	(PARAMETERS) support: C Yes No
[PICC5.11] (*) A	Ill AFIs are supported:
If	f not, indicate all supported AFI(s): Only AFI=0 is supported
[PICC5.12] (*) R	EOB/WUPB with N > 1 support: • Yes • No